


STATE OF MISSOURI
DEPARTMENT OF NATURAL RESOURCES
MISSOURI AIR CONSERVATION COMMISSION



PERMIT BOOK

PERMIT TO CONSTRUCT

Under the authority of RSMo 643 and the Federal Clean Air Act the applicant is authorized to construct the air contaminant source(s) described below, in accordance with the laws, rules and conditions as set forth herein.

Permit Number: **06 2 0 0 6 - 0 1 1** Project Number: **2006-03-093**
Owner: **Lafarge North America Inc.**
Owner's Address: **15100 E. Coutney Atherton Rd., Sugar Creek, MO 64058**
Installation Name: **Lafarge-Independence Quarry**
Installation Address: **16400 E. Kentucky Rd., Independence, MO 64058**
Location Information: **Jackson County, S19/24, T50N, R31W**


Application for Authority to Construct was made for:

The modification of an existing rock crushing plant. Rock is processed through 1 crusher(s), 2 screen(s), and 16 conveyor(s). The rock crushing plant has a maximum hourly design rate (MHDR) of 500.00 tons per hour (tph). Best Management Practices will be used in Independence Quarry Site to control fugitive emissions from storage piles and haul roads This review was conducted in accordance with Section (6), Missouri State Rule 10 CSR 10-6.060, *Construction Permits Required*.

-
- ☐ Standard Conditions (on reverse) are applicable to this permit.
- ☒ Standard Conditions (on reverse) and Special Conditions (listed as attachments starting on page 2) are applicable to this permit.

JUN 20 2006

EFFECTIVE DATE


DIRECTOR OR DESIGNEE
DEPARTMENT OF NATURAL RESOURCES

STANDARD CONDITIONS:

Permission to construct may be revoked if you fail to begin construction or modification within two years from the effective date of this permit. Permittee should notify the Air Pollution Control Program if construction or modification is not started within two years after the effective date of this permit, or if construction or modification is suspended for one year or more.

You will be in violation of 10 CSR 10-6.060 if you fail to adhere to the specifications and conditions listed in your application, this permit and the project review. Specifically, all air contaminant control devices shall be operated and maintained as specified in the application, associated plans and specifications.

You must notify the Air Pollution Control Program of the anticipated date of start up of this (these) air contaminant source(s). The information must be made available not more than 60 days but at least 30 days in advance of this date. Also, you must notify the Department of Natural Resources Regional Office responsible for the area within which you are located within 15 days after the actual start up of this (these) air contaminant source(s).

A copy of this permit and permit review shall be kept at the installation address and shall be made available to Department of Natural Resources' personnel upon request.

You may appeal this permit or any of the listed Special Conditions as provided in RSMo 643.075. If you choose to appeal, the Air Pollution Control Program must receive your written declaration within 30 days of receipt of this permit.

If you choose not to appeal, this certificate, the project review, your application and associated correspondence constitutes your permit to construct. The permit allows you to construct and operate your air contaminant source(s), but in no way relieves you of your obligation to comply with all applicable provisions of the Missouri Air Conservation Law, regulations of the Missouri Department of Natural Resources and other applicable federal, state and local laws and ordinances.

The Department of Natural Resources has established the Outreach and Assistance Center to help in completing future applications or fielding complaints about the permitting process. You are invited to contact them at 1-800-361-4827 or (573) 526-6627, or in writing addressed to Outreach and Assistance Center, P.O. Box 176, Jefferson City, MO 65102-0176.

The Air Pollution Control Program invites your questions regarding this air pollution permit. Please contact the Construction Permit Unit at (573) 751-4817. If you prefer to write, please address your correspondence to the Air Pollution Control Program, P.O. Box 176, Jefferson City, MO 65102-0176, attention Construction Permit Unit.

2006-03-093
095-0285

Lafarge North America Inc.

15100 E. Coutney Atherton Rd., Sugar Creek, MO 64058

Lafarge-Independence Quarry

16400 E. Kentucky Rd., Independence, MO 64058

Jackson County, S19/24, T50N, R31W

The modification of an existing rock crushing plant. Rock is processed through 1 crusher(s), 2 screen(s), and 16 conveyor(s). The rock crushing plant has a maximum hourly design rate (MHDR) of 500.00 tons per hour (tph). Best Management Practices will be used in Independence Quarry Site to control fugitive emissions from storage piles and haul roads This review was conducted in accordance with Section (6), Missouri State Rule 10 CSR 10-6.060, *Construction Permits Required*.

Page No.	2
Permit No.	
Project No.	2006-03-093

SPECIAL CONDITIONS:

The permittee is authorized to construct and operate subject to the following special conditions:

The special conditions listed in this permit were included based on the authority granted the Missouri Air Pollution Control Program by the Missouri Air Conservation Law (specifically 643.075); by the Missouri Rules listed in Title 10, Division 10 of the Codes of State Regulations (specifically 10 CSR 10-6.060); by 10 CSR 10-6.060 paragraph (12)(A)10. "Conditions required by permitting authority"; by 10 CSR 10-6.010 "Ambient Air Quality Standards" and 10 CSR 10-6.060 subsections (5)(D) and (6)(A); and by control measures requested by the applicant, in their permit application, to reduce the amount of air pollutants being emitted, in accordance with 10 CSR 10-6.060 paragraph (6)(E)3. Furthermore, one or more of the Subparts of 40 CFR Part 60, New Source Performance Standards (NSPS), applies to this installation.

1. **Best Management Practices**
Lafarge-Independence Quarry shall control fugitive emissions from all of the haul roads and stockpiles at this site by performing *Best Management Practices*, which include the usage of paving, chemical dust suppressants, or documented watering. These practices are defined in Attachment AA.
2. **National Ambient Air Quality Standards (NAAQS) Limitation for Particulate Matter Less Than Ten Microns in Diameter (PM₁₀)**
 - A. The operator(s) for Lafarge-Independence Quarry's rock crushing plant (095-0285) shall ensure, while operating at this site, that the ambient impact of PM₁₀ at or beyond the nearest property boundary does not exceed 150 µg/m³ in any 24-hour period, in accordance with the Federal NAAQS requirements (40 CFR 50.6).
 - B. To demonstrate compliance, the operator(s) shall maintain a daily record of material processed. Attachment A, *Daily Ambient PM₁₀ Impact Tracking Record*, or other equivalent form(s), will be used for this purpose.
3. **Moisture Content Testing Requirement for Inherent Moisture Content**
 - A. The inherent moisture content of the rock will reduce particulate emissions. Lafarge-Independence Quarry claimed the inherent moisture content of the processed rock to be greater than or equal to 1.5 wt%, which shall be verified by testing.
 - B. Testing shall be conducted according to approved methods, such as those prescribed by the *American Society for Testing Materials (ASTM D-2216 or C-566)*, EPA AP-42 Appendix C.2, or other method(s) approved by the Director. The first test shall be no later than 45 days after startup. Testing shall be conducted for three consecutive years during the months of June through September, while the rock crushing plant is active at this site. If the test results have been consistently greater than 1.5 wt% and there is no reported emission exceedances from the plant, then no further testing is required and this site shall be deemed to have met this condition on all subsequent permits. Verification of the results will be performed during a routine inspection. If the test results have been less than 1.5 wt% and/or there is substantial change in the emissions from the plant, then Lafarge-Independence Quarry shall apply for a new construction permit to account for the revised information or operate a wet suppression system capable of maintaining visible emissions standards for each unit within 30 days.
 - C. The operator shall obtain test samples before processing (before entering the Primary Crusher, EP01) and after processing (prior to load-in to bins and/or storage piles). During the sample processing run only, any spray devices shall be turned off during the processing from which test samples are obtained. The written analytical report shall include the raw data and moisture content (wt.%) of each sample, the test date, and the original signature of the individual performing the test. Records shall be maintained on site and/or Lafarge – Independence Quarry's Central Office. These records shall be made available to Department of Natural Resources personnel upon request..
 - D. If the inherent moisture content result of the first test is less than 1.5 wt.%, a second test must be performed within 30 days. If the result of the second test is less than 1.5 wt.%, Lafarge – Independence Quarry shall apply for a new construction permit to account for the revised information or install wet spray devices on the affected units.
4. **Prohibition Against Concurrent Operations Without Further APCP Review**
 - A. The rock crushing plant (095-0285) is prohibited from operating whenever any other plant(s) are located at this site.

Page No.	3
Permit No.	
Project No.	2006-03-093

SPECIAL CONDITIONS:

The permittee is authorized to construct and operate subject to the following special conditions:

5. **Restriction on Process Configuration of Primary Emission Point(s)**
The maximum hourly design rate of the plant is equal to the sum of the design rate(s) of the primary emission point(s). Lafarge-Independence Quarry has designated the following unit(s) as the primary emission point(s) of the rock crushing plant: primary crusher. Bypassing the primary emission point(s) for processing is prohibited.
6. **Restriction on Minimum Distance to Nearest Property Boundary**
The primary emission point of the rock crushing plant, which is the primary crusher, shall be located at least 550 feet from the nearest property boundary whenever it is operating at this site.
7. **Restriction on Diesel Engine**
Diesel Engine can only operate while plant is running.
8. **Record Keeping Requirement**
The operator(s) shall maintain all records required by this permit for not less than five (5) years and shall make them available immediately to any Missouri Department of Natural Resources' personnel upon request.
9. **Reporting Requirement**
The operator(s) shall report to the Air Pollution Control Program (APCP) Enforcement Section, P.O. Box 176, Jefferson City, MO 65102, no later than ten (10) days after any exceedances of the limitations imposed by this permit.
10. **Superseding Condition**
The conditions of this permit supersede all special conditions found in the previously issued construction permit(s) (072000-019) from the Air Pollution Control Program.

TECHNICAL REVIEW OF APPLICATION FOR AUTHORITY TO CONSTRUCT

PROJECT DESCRIPTION

Lafarge requested modification of this site permit to include Best Management Practices. Rock, composed of non-metallic minerals, is drilled/blasted, loaded into haul trucks, and transported to processing. Rock is processed through feeder(s), crusher(s), screen(s), conveyor(s), and bin(s). Processing equipment is powered with diesel engine(s). The emission points are listed in the attached spreadsheet summary. This installation is not on the List of Named Installations [10 CSR 10-6.020(3)(B), Table 2]. The installation is located in Jackson County, an attainment area for all criteria air pollutants.

EMISSIONS EVALUATION

Criteria air pollutants will be emitted from this operation. The main air pollutant of concern is PM₁₀. The potential emissions were calculated from the maximum hourly design rate (MHDR) of the equipment, appropriate emission factors, control device efficiencies, and the limiting operating hours at MHDR. The sources of the emission factors and control efficiencies are listed in the section "Permit Documents". HP Heat input to output efficiency is 35. Based on the conditioned potential emissions, the operation is considered a minor source under 10 CSR 10-6.060 section (6).

Table 1: Emissions Summary (tons per year)

Air Pollutant	Regulatory De Minimis Levels	*Existing Potential Emissions	Existing Actual Emissions (year EIQ)	Potential Emissions of the Application	**New Installation Conditioned Potential	Emission Factor (lb/ton)
PM ₁₀	15.0	39	14.3	75.22	45.7405	N/A
SO _x	40.0	N/A	N/A	9.86	5.99	N/A
NO _x	40.0	N/A	N/A	149.91	91.16	N/A
VOC	40.0	N/A	N/A	12.24	7.44	N/A
CO	100.0	N/A	N/A	32.29	19.64	N/A
HAPs	10.0/25.0	N/A	N/A	0.13	0.08	N/A

Note: N/A = Not Applicable.

* Existing potential emissions taken from permit # 072000-019

** Conditioned potential based on daily production limit from ambient impact analysis. Other pollutants proportionately reduced.

AMBIENT AIR QUALITY IMPACT ANALYSIS

Screening tools were used to evaluate the ambient air impact of the hourly emissions from this operation. The ambient impact was evaluated at a distance of 550 feet to the nearest property boundary. The ambient impact at this site shall not exceed the National Ambient Air Quality Standard (NAAQS) of 150 µg/m³ of PM₁₀ at or beyond the nearest property boundary in any single 24-hour period. The screening tools were used to develop an ambient impact factor for the rock crushing plant. This ambient impact factor is incorporated into the daily record keeping table, Attachment A.

For sources agreeing to use Best Management Practices (BMPs), as defined in Attachment AA, haul roads and stockpiles are not modeled with screening tools. Instead, they are addressed as a background level of 20 µg/m³ of PM₁₀. To ensure conformity with NAAQS, the remaining process emissions are limited to an impact of less than 130 µg/m³ of PM₁₀ at or beyond the nearest property boundary.

Table 2: Ambient Air Quality Impact Analysis of PM₁₀, 24-Hour Averaging Time

Operation	Ambient Impact Factor (µg/m ³ ton)	Modeled Impact (µg/m ³)	*Background (µg/m ³)	NAAQS (µg/m ³)	Daily Production Limit (tons)
1. Solitary	0.0178	129.90	20.00	150.00	7,296.89

Background PM₁₀ level of 20.00 µg/m³ from haul roads and stockpiles.

Ambient air quality modeling was performed to determine the ambient impact of Nitrogen Dioxide (NO_x). site has one (1) generator no closer than 550 feet to the nearest property boundary. Ambient impact modeling was performed using screen view the interface for EPA Screen 3 Model. The results of this modeling show the site is in compliance with the annual concentration of NO_x at their property boundary when the generator is 550 feet from the property boundary.

Pollutant	Modeled Impact (µg/m ³)	NAAQS (µg/m ³)	Time Period)
NO _x	31.35	100.00	Annual

APPLICABLE REQUIREMENTS

The owner is subject to compliance with the following applicable requirements. The Missouri Air Conservation Laws and Regulations should be consulted for specific record keeping, monitoring, and reporting requirements.

- *Submission of Emission Data, Emission Fees and Process Information*, 10 CSR 10-6.110
- *Operating Permits*, 10 CSR 10-6.065
- An Operating Permit application is required for this installation within 30 days of equipment startup.
- *Restriction of Particulate Matter to the Ambient Air Beyond the Premises of Origin*, 10 CSR 10-6.170
- *Restriction of Emission of Visible Air Contaminants*, 10 CSR 10-6.220
- *Restriction of Emission of Odors*, 10 CSR 10-3.090
- *Restriction of Emission of Particulate Matter From Industrial Processes*, 10 CSR 10-6.400
- *Restriction of Emission of Sulfur Compounds*, 10 CSR 10-6.260
- 40 CFR Part 60 Subpart "OOO", *Standards of Performance for Nonmetallic Mineral Processing Plants*, of the New Source Performance Standards (NSPS)
- The National Emission Standards for Hazardous Air Pollutants (NESHAPs) and the currently promulgated Maximum Achievable Control Technology (MACT) regulations do not apply to the proposed equipment.

STAFF RECOMMENDATION

On the basis of this review conducted in accordance with Section (6), Missouri State Rule 10 CSR 10-6.060, *Construction Permits Required*, I recommend this permit be granted with special conditions.

Samer Al-Shoukhi
Environmental Engineer

Date

PERMIT DOCUMENTS

The following documents are incorporated by reference into this permit:

- The Application for Authority to Construct form, designating Lafarge North America Inc. as the owner and operator of the installation.
- Environmental Protection Agency (EPA) AP-42, *Compilation of Air Pollutant Emission Factors; Volume I, Stationary Point and Area Sources, Fifth Edition*.
- Noyes Data Corp. book, Orlemann, et al.1983, *Fugitive Dust Control*.
- EPA Factor Information Retrieval (FIRE) Version 6.21.
- Spreadsheet calculations of potential-to-emit and ambient impact.
- Kansas City Regional Office Site Survey.
- Best Management Practices

Attachment A: Daily Ambient PM₁₀ Impact Tracking Record
Lafarge-Independence Quarry, 095-0285 – Rock Crushing Plant
Solitary Operation

Project Number: 2006-03-093
 County, CSTR: Jackson County (S19/24, T50N, R31W)
 Primary Unit Size: 500 tph
 Distance to Nearest Property Boundary: 550 feet

This sheet covers the period from _____ to _____ (Month, Day, Year) *(Copy this sheet as needed.)*

Date	Lafarge-Independence Quarry 095-0285 Project # 2006-03-093			Plant Name: Plant ID: Permit #:			Plant Name: Plant ID: Permit #:			Plant Name: Plant ID: Permit #:			² Back-ground PM ₁₀ Level (µg/m ³)	³ TOTAL PM ₁₀ Level (µg/m ³)
	Daily Production (tons)	Ambient Impact Factor (µg/m ³ /ton)	¹ Daily PM ₁₀ Impact (µg/m ³)	Daily Production (tons)	Ambient Impact Factor (µg/m ³ /ton)	¹ Daily PM ₁₀ Impact (µg/m ³)	Daily Production (tons)	Ambient Impact Factor (µg/m ³ /ton)	¹ Daily PM ₁₀ Impact (µg/m ³)	Daily Production (tons)	Ambient Impact Factor (µg/m ³ /ton)	¹ Daily PM ₁₀ Impact (µg/m ³)		
		0.0178		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	20.00	
		0.0178		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	20.00	
		0.0178		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	20.00	
		0.0178		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	20.00	
		0.0178		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	20.00	
		0.0178		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	20.00	
		0.0178		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	20.00	
		0.0178		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	20.00	
		0.0178		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	20.00	
		0.0178		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	20.00	
		0.0178		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	20.00	
		0.0178		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	20.00	
		0.0178		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	20.00	
		0.0178		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	20.00	
		0.0178		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	20.00	
		0.0178		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	20.00	
		0.0178		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	20.00	
		0.0178		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	20.00	
		0.0178		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	20.00	
		0.0178		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	20.00	

Note 1: The Daily PM₁₀ Impact (µg/m³) for each plant is calculated by multiplying the Daily Production (tons) by the matching Ambient Impact Factor.

Note 2: Background PM₁₀ Level of 20 (µg/m³) is from Haul Roads and Stockpiles.

Note 3: The TOTAL PM₁₀ Level (µg/m³) is calculated by summing the Daily PM₁₀ Ambient Impact(s) and the Background PM₁₀ Level. A TOTAL PM₁₀ Level of less than 150 µg/m³ in any 24-hour period indicates compliance.

Attachment AA: Best Management Practices (BMPs)- Construction Industry Fugitive Emissions

Construction Industry Sites covered by the Interim Relief Policy shall maintain Best Management Control Practices (BMPs) for fugitive emission areas at their installations when in operation. Options for BMPs are at least one of the following:

For Haul Roads:

1. Pavement of Road Surfaces –
 - A. The operator(s) may pave all or any portion of the haul roads with materials such as asphalt, concrete, and/or other material(s) after receiving approval from the program. The pavement will be applied in accordance with industry standards for such pavement so as to achieve “Control of Fugitive Emissions¹” while the plant is operating.
 - B. Maintenance and/or repair of the road surface will be conducted as necessary to ensure that the physical integrity of the pavement is adequate to achieve control of fugitive emissions from these areas while the plant is operating.
 - C. The operator(s) shall periodically water, wash and/or otherwise clean all of the paved portions of the haul road(s) as necessary to achieve control of fugitive emissions from these areas while the plant is operating.
2. Usage of Chemical Dust Suppressants –
 - A. The operator(s) shall apply a chemical dust suppressant (such as magnesium chloride, calcium chloride, lignosulfonates, etc.) to all the unpaved portions of the haul roads. The suppressant will be applied in accordance with the manufacturer’s suggested application rate (if available) and re-applied as necessary to achieve control of fugitive emissions from these areas while the plant is operating.
 - B. The quantities of the chemical dust suppressant shall be applied, re-applied and/or maintained sufficient to achieve control of fugitive emissions from these areas while the plant is operating.
 - C. The operator(s) shall record the time, date and the amount of material applied for each application of the chemical dust suppressant agent on the above areas. The operator(s) shall keep these records with the plant for not less than five (5) years, and the operator(s) shall make these records available to Department of Natural Resources personnel upon request.
3. Usage of Documented Watering –
 - A. The operator(s) shall control the fugitive emissions from all the unpaved portions of the haul roads at the installation by consistently and correctly using the application of a water spray. Documented watering will be applied in accordance with a recommended application rate of 100 gallons per day per 1,000 square feet of unpaved/untreated surface area of haul roads as necessary to achieve control of fugitive emissions from these areas while the plant is operating. For example, the operator(s) shall calculate the total square feet of unpaved vehicle activity area requiring control on any particular day, divide that product by 1,000, and multiply the quotient by 100 gallons for that day.
 - B. The operator(s) shall maintain a log that documents daily water applications. This log shall include, but is not limited to, date and volumes (e.g., number of tanker applications and/or total gallons used) of water application. The log shall also record rationale for not applying water on day(s) the plant is in operation (e.g., meteorological situations, precipitation events, freezing, etc.)
 - C. Meteorological precipitation of any kind, (e.g. a quarter inch or more rainfall, sleet, snow, and/or freeze thaw conditions) which is sufficient in the amount or condition to achieve control of fugitive emissions from these areas while the plant is operating.
 - D. Watering may also be suspended when the ground is frozen, during periods of freezing conditions when watering would be inadvisable for traffic safety reasons, or when there will be no traffic on the roads. The operator(s) shall record a brief description of such events in the same log as the documented watering.
 - E. The operator(s) shall record the date and the amount of water applied for each application on the above areas. The operator(s) shall keep these records with the plant for not less than five (5) years, and the operator(s) shall make these records available to Department of Natural Resources personnel upon request.

¹ For purposes of this document, Control of Fugitive Emissions means to control particulate matter that is not collected by a capture system and visible emissions to the extent necessary to prevent violations of the air pollution law or regulation. (Note: control of visible emission is not the only factor to consider in protection of ambient air quality.)

For Vehicle Activity Areas around Open Storage Piles:

1. Pavement of Stockpile Vehicle Activity Surfaces –
 - A. The operator(s) may pave all or any portion of the vehicle activity areas around the storage piles with materials such as asphalt, concrete, and/or other material(s) after receiving approval from the program. The pavement will be applied in accordance with industry standards for such pavement so as to achieve control of fugitive emissions while the plant is operating.
 - B. Maintenance and/or repair of the road surface will be conducted as necessary to ensure that the physical integrity of the pavement is adequate to achieve control of fugitive emissions from these areas while the plant is operating.
 - C. The operator(s) shall periodically water, wash and/or otherwise clean all of the paved portions of the vehicle activity areas around the storage piles as necessary to achieve control of fugitive emissions from these areas while the plant is operating.
2. Usage of Chemical Dust Suppressants –
 - A. The operator(s) shall apply a chemical dust suppressant (such as magnesium chloride, calcium chloride, lignosulfonates, etc.) to all the vehicle activity areas around the open storage piles. The suppressant will be applied in accordance with the manufacturer's suggested application rate (if available) and re-applied as necessary to achieve control of fugitive emissions from these areas while the plant is operating.
 - B. The quantities of the chemical dust suppressant shall be applied, re-applied and/or maintained sufficient to achieve control of fugitive emissions from these areas while the plant is operating.
 - C. The operator(s) shall record the time, date and the amount of material applied for each application of the chemical dust suppressant agent on the above areas. The operator(s) shall keep these records with the plant for not less than five (5) years, and the operator(s) shall make these records available to Department of Natural Resources personnel upon request.
3. Usage of Documented Watering –
 - A. The operator(s) shall control the fugitive emissions from all the vehicle activity areas around the storage piles at the installation by consistently and correctly using the application of a water spray. Documented watering will be applied in accordance with a recommended application rate of 100 gallons per day per 1,000 square feet of unpaved/untreated surface area of vehicle activity areas around the storage piles as necessary to achieve control of fugitive emissions from these areas while the plant is operating. (Refer to example for documented watering of haul roads.)
 - B. The operator(s) shall maintain a log that documents daily water applications. This log shall include, but is not limited to, date and volumes (e.g., number of tanker applications and/or total gallons used) of water application. The log shall also record rationale for not applying water on day(s) the plant is in operations (e.g., meteorological situations, precipitation events, freezing, etc.)
 - C. Meteorological precipitation of any kind, (e.g. a quarter inch or more rainfall, sleet, snow, and/or freeze thaw conditions) which is sufficient in the amount or condition to achieve control of fugitive emissions from these areas while the plant is operating.
 - D. Watering may also be suspended when the ground is frozen, during periods of freezing conditions when watering would be inadvisable for traffic safety reasons, or when there will be no traffic on the roads. The operator(s) shall record a brief description of such events in the same log as the documented watering.
 - E. The operator(s) shall record the date and the amount of water applied for each application on the above areas. The operator(s) shall keep these records with the plant for not less than five (5) years, and the operator(s) shall make these records available to Department of Natural Resources personnel upon request.

Mr. Jonathan Sommer
Resource Management Coordinator
Lafarge North America Inc.
15100 E. Coutney Atherton Rd.
Sugar Creek, MO 64058

RE: New Source Review Permit - Project Number: 2006-03-093

Dear Mr. Sommer:

Enclosed with this letter is your New Source Review permit. Please review your permit carefully and note the special conditions, if any, and the requirements in your permit.

Operation in accordance with the conditions and requirements in your permit, the New Source Review application submitted for project 2006-03-093, and your amended operating permit, if required, is necessary for continued compliance. Please review your amended operating permit, as it will contain all applicable requirements for your rock crushing plant, including any special conditions from your New Source Review permit.

The section of the permit entitled "Technical Review of Application for Authority to Construct" should not be separated from the main portion of your permit. The entire permit must be retained in your files. The reverse side of your permit certificate has important information concerning standard permit conditions and your rights and obligations under the laws and regulations of the State of Missouri.

If you have any questions regarding this permit, please do not hesitate to contact me at (573) 751-4817, or you may write to the Department of Natural Resources' Air Pollution Control Program, P.O. Box 176, Jefferson City, Missouri 65102. Thank you for your attention to this matter.

Sincerely,

AIR POLLUTION CONTROL PROGRAM

Kendall B. Hale,
Initial Review Unit Chief

KBH:sal

Enclosures

c: Kansas City Regional Office
PAMS File: 2006-03-093
Permit Number: